

a flanged joint. Piping may be carried through bunker spaces and deep tanks provided it is run through a pipe tunnel. The tunnel may be omitted where the pipe is extra heavy, all joints are welded, and bends are installed to provide for expansion and contraction.

(b) Cargo piping shall not pass through spaces containing machinery where sources of vapor ignition are normally present: *Provided*, That in special cases the Commandant may permit the piping to pass through such spaces if Grade E liquids only are involved.

(c) Valve operating rods in the cargo tanks shall be solid and of ample size, well guided and supported, and attached to the valve stems in a manner to guard against their working loose. Where such valve rods pass through the deck, gas tight stuffing boxes shall be fitted. The leads of valve rods shall be as direct as possible. All valves and fittings shall be of material, design, and manufacture for the intended service on the cargo system; either rising or nonrising stem valves may be used.

§ 32.50-25 Cargo pumps and piping on tank vessels constructed prior to November 10, 1936—TB/ALL.

On tank vessels, the construction or conversion of which was started prior to November 10, 1936, cargo pumps and piping which do not fully comply with the regulations in this subchapter shall be made as nearly equal to the requirements for tank vessels constructed between November 10, 1936, and July 1, 1951, as is necessary in the interest of safety. Cargo pipe lines may pass through cargo pump engine compartments provided no cargo valves are located therein.

§ 32.50-30 Cargo hose—TB/ALL.

Cargo hose carried on tank vessels must be suitable for oil service and designed to withstand the pressure of the shutoff head of the cargo pump or pump relief valve setting, less static head, but in no case less than 150 pounds per square inch.

NOTE: For additional requirements concerning cargo hose, see 33 CFR 154.500, 155.800 and 156.170.

[CGD 80-009, 48 FR 36458, Aug. 11, 1983]

§ 32.50-35 Remote manual shutdown for internal combustion engine driven cargo pump on tank vessels—TB/ALL.

(a) Any tank vessel which is equipped with an internal combustion engine driven cargo pump on the weather deck shall be provided with a minimum of one remote manual shutdown station, conspicuously marked, and located at the midpoint of such vessel, or 100 feet from the engine, whichever is the more practical. The remote quick acting manual shutdown shall be installed on the engine so as to provide a quick and effective means of stopping the engine (such as by cutting off the intake air).

(b) This regulation applies to all installations of this type on tank vessels, but for such installations now on existing tankships at the date of next biennial inspection or October 1, 1963, whichever occurs later.

Subpart 32.52—Bilge Systems

§ 32.52-1 Bilge pumps on tank vessels constructed or converted on or after November 19, 1952—TB/ALL.

The number and arrangement of bilge pumps on each tank vessel shall conform to the requirements of subchapter F (Marine Engineering) of this chapter, except as hereinafter provided in this subpart.

§ 32.52-5 Bilge piping for pump rooms and adjacent cofferdams on tank vessels constructed or converted on or after November 19, 1952—TB/ALL.

(a) Provisions shall be made for removing drainage from the pumproom bilges and adjacent cofferdams. A separate bilge pump, ejector, or bilge suction from a cargo pump or cargo stripping pump may be provided for this purpose. The bilge pump shall not be located in nor shall the piping pass through spaces containing machinery where sources of vapor ignition are normally present.

(b) Where a bilge suction is provided from a cargo or stripping pump, a stopcheck valve shall be fitted in the suction branch, and an additional stop valve shall be fitted also if the bilge suction branch can be subjected to a head of oil from the filling line.

§ 32.52-10

(c) Means shall be provided for controlling the cargo or pump room bilge pumps and their suctions or discharges in order that a flooded pump room may be pumped out. Suitable portable or manually operated pumps may be accepted as complying with this provision, or alternatively, the pump controls shall be arranged so that they are operable from inside the pump room and either from an accessible position outside the pump room, or from the pump room casing above the freeboard deck.

§ 32.52-10 Bilge pumps and piping on tank vessels constructed or converted prior to November 19, 1952—TB/ALL.

(a) On tank vessels, the construction or conversion of which was started prior to November 19, 1952, bilge pumps and piping which do not fully comply with the regulations of this subchapter shall be made as nearly equal to the requirements for tank vessels constructed on or after November 19, 1952, as is necessary in the interest of safety.

(b) Bilge suctions from hold spaces containing independent cargo tanks may be connected to cargo pumps or stripping pumps, provided the installation complies with the requirements of § 32.52-5(b).

Subpart 32.53—Inert Gas System

SOURCE: CGD 74-127, 41 FR 3843, Jan. 26, 1976, unless otherwise noted.

§ 32.53-1 Application—T/ALL.

(a) Except as provided in paragraphs (b) and (c) of this section, this subpart applies to:

(1) A U.S. crude oil tanker or product carrier of 100,000 DWT tons (metric) or more or combination carrier of 50,000 DWT tons (metric) or more, that has a keel laying date on or after January 1, 1975.

(2) A new (as defined in 46 U.S.C. 3701) crude oil tanker or product carrier, or foreign flag crude oil tanker or product carrier of 20,000 DWT tons or more entering the navigable waters of the U.S.

(3) A crude oil tanker that is equipped with a cargo tank cleaning system that uses crude oil washing.

46 CFR Ch. I (10-1-04 Edition)

(4) An existing product carrier of 20,000 deadweight tons (metric) or more that has tank washing machines with a capacity of more than 60 cubic meters per hour after May 31, 1983.

(5) Any other U.S. or foreign flag:

(i) Crude oil tanker or product carrier of 70,000 deadweight tons (metric) and over after May 31, 1981;

(ii) Crude oil tanker between 20,000 and 70,000 deadweight tons (metric) after May 31, 1983;

(iii) Product carrier between 40,000 and 70,000 deadweight tons (metric) after May 31, 1983.

(b) This subpart does not apply to vessels designed to carry only:

(1) Liquefied gas cargo; or

(2) Grade E cargo that is carried at a temperature lower than 5° C below its flash point.

(c) This part does not apply to vessels as stated in 46 U.S.C. 3702.

[CGD 77-057a, 44 FR 66501, Nov. 19, 1979, as amended by CGD 97-057, 62 FR 51043, Sept. 30, 1997; CGD 95-028, 62 FR 51198, Sept. 30, 1997]

§ 32.53-3 Exemptions.

(a) The Assistant Commandant for Marine Safety and Environmental Protection grants exemptions for crude oil tankers of less than 40,000 deadweight tons not fitted with high capacity tank washing machines, if the vessel's owner can show that compliance would be unreasonable and impracticable due to the vessel's design characteristics.

(b) Requests for exemptions must be submitted in writing to: Commandant (G-MSO), U.S. Coast Guard, Washington, DC 20593-0001.

(c) Each request must be supported by documentation showing that:

(1) The system would be detrimental to the safe operation of the vessel;

(2) It is physically impracticable to install the system; or

(3) Adequate maintenance of the system would be impossible.

(d) The vessel's owner may request a conference. The exemption request file will be available for use in the conference and additional arguments or evidence in any form may be presented. The conference will be recorded. The presiding officer summarizes the material presented at the conference and submits written recommendations to